Installation Sheet) KSRDL102

Twist & Lock (

Recessed Tiltable Downlight

retain them for future reference. Read these instructions before commencing installation &

IP20 <a>[] <a>[]

These Fittings are Class II: Double insulated, No Earth required

Important Information

the IEE wiring regulations BS7671. The installation of this product must comply with the current edition of It is recommended that luminaires are installed by a qualified electrician

KSR will not accept responsibility for any claims arising from a poor Any damaged parts should be replaced as soon as possible. These products are designed for connection to a 240V 50Hz supply.

Important User Advice

installation

voltage and wattage. Always switch off mains supply before servicing, fitting or changing lamp. Check the lamp is correct for the application, including its

on electricity at mains Ensure that the lamp is correctly located in the lampholder. Switch

Installation Details

Connect this product to a mains 240V 50Hz supply. void without infringing on joists, water pipes or electrical cables. Cut a round hole in ceiling and ensure adequate minimum ceiling

onto new plaster or damp areas. Fit this product as per the illustration shown in (Fig 1). Do not fit

connector to lampholder has two thickness of insulation. This appliance will be considered Class II, the cabling from





front of the fitting. be at least 0.5m distance from the ventilation around fitting. The nearest illuminated surface must *Ensure there is adequate free air







| Max Wattage |
|-------------|

