E-mail: info@ksr-lighting.co.uk

KSR Lighting Aftersales: 023 92 674343

KSR7115 Warm White 3000K 330 Lumens KSR7116 Warm White 3000K 330 Lumens

Details LED Fixed Module







































134 m r

Fig. 1

Available Finish: Stainless Steel

Fuente

LED Walkover Light



required placed in a protective conduit.

Once you are satisfied:

KSR recommends that you familiarise yourself with the installation

ranges life span will be effected (reduced).

Installation Procedure

Always switch off mains supply before servicing.

The working ambient temperature should be -20°C \sim +40°C if outside these

Important User Advice

KSR will not accept responsibility for any claims arising from a poor installation.

Any broken or damaged parts should be replaced as soon as possible

These products are designed for connection to a 240v AC Supply

the installation complies to current IEE wiring regulations & local building control.

It is recommended that luminaires are installed by a qualified electrician ensuring

Important Information

mains supply using a suitable IP rated connector i.e.KSR3184 (not supplied Offer the main body of the fitting to the ground pot and connect the luminaire to the immersed in water once installed (Fig. 1). It is advised the the bezel fixings are lightly greased to allow for easy removal in the

luture

Turn on mains supply and test luminaire is working correctly

135mm-

134 m m

Read these instructions before commencing installation & Installation Sheet

retain them for future reference

1P67 🕀 🤇 🧲 240V 5W LEC

KSR7115-16