

Morphis I LED Post Lantern

Urban Lighting



Product Information

The Morphis I LED Street Post lantern Range are a Traditional style lantern range available in 5 different versions in either Anthracite or Antique Bronze.

This range is perfect for domestic, Commercial and external applications

Product Features

- 2 year warranty
- Class I
- IP65
- CRI: Ra80
- 24w 3000K/5000K LED options
- Integral LED Driver is non-dimmable
- Service Door located in Base
- Available in Anthracite and Antique Bronze
- See Morphis I LED lantern Range for matching lanterns





KSR3566 ANTH

Product Specification

| Product Code | Product Description | Wattage (W) | ССТ (К) | Lumens (Im) | Energy Efficiency 2021 | Protection Class |
|-----------------|---|----------------|---------|----------------|------------------------------|---------------------|
| KSR3556 | Morphis I 24w 5000K LED 1.8m Single Street Post Lantern | 24 | 5000 | 2880 | E | 1 |
| KSR3557 | Morphis I 24w 3000K LED 1.8m Single Street Post Lantern | 24 | 3000 | 1900 | E | Ι |
| KSR3558 | Morphis I 24w 5000K LED 3m Single Street Post Lantern | 24 | 5000 | 2880 | E | I |
| KSR3559 | Morphis I 24w 3000K LED 3m Single Street Post Lantern | 24 | 3000 | 1900 | E | I |
| KSR3560 | Morphis I 2x24w 5000K LED 3.3m Twin Street Post Lantern | 2x24 | 5000 | 2x2880 | E | I |
| KSR3561 | Morphis I 2x24w 3000K LED 3.3m Twin Street Post Lantern | 2x24 | 3000 | 2x1900 | E | Ι |
| KSR3562 | Morphis I 3x24w 5000K LED 3.3m Triple Street Post Lantern | 3x24 | 5000 | 3x2880 | E | I |
| KSR3563 | Morphis I 3x24w 3000K LED 3.3m Triple Street Post Lantern | 3x24 | 3000 | 3x1900 | E | I |
| KSR3564 | Morphis I 2x24w 5000K LED 3.3m Downward Twin Street Post Lantern | 2x24 | 5000 | 2x2880 | E | I |
| KSR3565 | Morphis I 2x24w 3000K LED 3.3m Downward Twin Street Post Lantern | 2x24 | 3000 | 2x1900 | E | I |
| KSR3566 | Morphis I 3x24w 5000K LED 3.3m Downward Triple Street Post Lantern | 3x24 | 5000 | 3x2880 | E | I |
| KSR3567 | Morphis I 3x24w 3000K LED 3.3m Downward Triple Street Post Lantern | 3x24 | 3000 | 3x1900 | E | 1 |

| Nominal voltage | 220~240VAC |
|---------------------|----------------|
| Operating frequency | 50-60Hz |
| Circuit Power | 24w |
| Temperature Range | -10°c to 40 °c |
| IP rating | 65 |

Construction

| Body: | Cast Aluminium |
|-----------|---------------------------|
| Diffuser: | Transparent Polycarbonate |

Standards

BSEN60598-1:2021 Luminaires – Part 1: General requirements and tests

In Conformity with

| LVD | Low voltage directive 2014/35/EU |
|------|---|
| RoHS | Restriction of hazardous substances 2015/863/EU |

www.ksrlighting.com

Product Dimensions

KSR3556-3557



KSR3558-3559



KSR3560-3561



KSR3562-3563



www.ksrlighting.com

Product Dimensions continued

KSR3564-3565



KSR Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and KSR may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, KSR Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.

www.ksrlighting.com

KSR Morphis I LED Street Post Lantern Range - DS – 15th July 2021

KSR3566-3567